


COOPERTIRES



Discoverer ATR

The **Discoverer ATR** features advanced sipes and an intersected tread element to deliver excellent traction in the wet. Increased tread block stiffness gives greater traction and handling. Available in black sidewall or outline white letters.





Discoverer ATR

Vtech Optimized Tyre Profile: Using state-of-the-art Vtech computer aided engineering, a mould profile was designed to provide favourable balance of wear and handling characteristics.

Chamfered Tread Elements: As part of their refined shape, the tread elements are strategically chamfered at the sawtooth circumferential grooves and also at the tip of the centre elements to increase element stability to fight irregular wear.


Extensive 'Zig-Zag' Siping: The extensive number of sipes on the centre rib and tread elements are deep to provide for long, dependable traction in all-weather conditions while the 'zig-zag' shape increases the effectiveness of the gripping edges.

RATING	KM/H	MPH
N	140	87
Q	160	99
R	170	106

RATING	KM/H	MPH
S	180	112
T	190	118
H	210	130

RATING	KM/H	MPH
V	240	149
W	270	168
Y	300	186

1 Five Rib All Terrain Design: Provides solid all-terrain performance.



For speed symbols V,W & Y load capacity reductions of up to 15% apply, above 210 Km/h for V-rated tyres, 240 Km/h for W-rated tyres & 270 Km/h for Y-rated tyres. Please consult Cooper Tire & Rubber Company for further information.



60%
ON ROAD

40%
OFF ROAD

- XL** Extra Load
- Black Sidewall
- W Outline White Letter

M+S RATED

SYMBOLS KEY

- sd SERVICE DESCRIPTION
- W RECOMMENDED RIM WIDTH
- APPROVED RIM WIDTH - MIN/MAX
- SECTION WIDTH
- OVERALL DIAMETER

Discoverer ATR

55 Series					
275/55R20XL W	117S	8.5	7.5 - 9.5	284	810
60 Series					
235/60R17 W	102T	7.0	6.5 - 8.5	240	714
65 Series					
235/65R17 W	104T	7.0	6.5 - 8.5	240	738
245/65R17 W	107S	7.0	7.0 - 8.5	248	750
255/65R17 W	110S	7.5	7.0 - 9.0	260	764
265/65R17 W	112T	8.0	7.5 - 9.5	272	776
LT275/65R18 W	123/120S	8.0	7.5 - 9.5	279	815
70 Series					
225/70R14 W	99S	6.5	6.0 - 7.5	228	672
205/70R15 W	96T	6.0	5.0 - 7.0	209	669
225/70R15 W	100S	6.5	6.0 - 7.5	228	697
235/70R15 W	103S	7.0	6.0 - 8.0	240	711
255/70R15 W	108S	7.5	6.5 - 8.5	260	739
265/70R15 W	112S	8.0	7.0 - 9.0	272	753
215/70R16 W	100S	6.5	5.5 - 7.0	221	708
225/70R16 W	102S	6.5	6.0 - 7.5	228	722
235/70R16 W	106T	7.0	6.0 - 8.0	240	736
245/70R16 W	107S	7.0	6.5 - 8.0	248	750
255/70R16 W	111S	7.5	6.5 - 8.5	260	764
265/70R16 W	112T	8.0	7.0 - 9.0	272	778
235/70R17XL W	111S	7.0	6.0 - 8.0	240	736
245/70R17 W	110S	7.0	6.5 - 8.0	248	776
255/70R17 W	112S	7.5	6.5 - 8.5	260	790
265/70R17 W	115S	8.0	7.0 - 9.0	272	804
265/70R18 W	116S	8.0	7.0 - 9.0	272	829
LT255/70R16 W	108/104R	7.5	6.5 - 8.5	260	764
LT305/70R16 W	118/115R	9.0	8.0 - 10.0	311	834
LT265/70R17 W	112/109R	8.0	7.0 - 9.0	272	804
LT265/70R17 W	121/118R	8.0	7.0 - 9.0	272	804
LT275/70R17 W	114/110R	8.0	7.0 - 9.0	279	818
LT285/70R17 W	121/118R	8.5	7.5 - 9.5	292	832
LT315/70R17 W	121/118R	9.5	8.5 - 10.0	323	874
LT275/70R18 W	125/122S	8.0	7.0 - 9.0	279	843
75 Series					
P205/75R15 W	97S	5.5	5.0 - 7.0	203	689
P215/75R15 W	100S	6.0	5.5 - 7.0	216	703
P225/75R15 W	102S	6.0	6.0 - 7.5	223	719
P235/75R15 W	105S	6.5	6.0 - 8.0	235	733
P235/75R15XL W	109S	6.5	6.0 - 8.0	235	733
P265/75R15 W	112S	7.5	7.0 - 9.0	267	779
P225/75R16 W	104S	6.0	6.0 - 7.5	223	744
P235/75R16 W	108S	6.5	6.0 - 8.0	235	758
P245/75R16 W	111S	7.0	6.5 - 8.0	248	774
P265/75R16 W	116S	7.5	7.0 - 9.0	267	804
LT235/75R15 W	104/101R	6.5	6.0 - 8.0	235	733
LT225/75R16 ●	110/107R	6.0	6.0 - 7.5	223	744
LT225/75R16 ●	115/112R	6.0	6.0 - 7.5	223	744
LT245/75R16 W	108/104R	7.0	6.5 - 8.0	248	774
LT245/75R16 ● W	120/116R	7.0	6.5 - 8.0	248	774
LT265/75R16 W	112/109R	7.5	7.0 - 9.0	267	804
LT265/75R16 W	123/120R	7.5	7.0 - 9.0	267	804
LT285/75R16 W	122/119R	8.0	7.5 - 9.5	286	834
LT315/75R16 W	121R	8.5	8.0 - 10.5	313	878
LT245/75R17 W	121/118S	7.0	6.5 - 8.0	248	800
80 Series					
LT235/80R17 W	120/117R	6.5	6.0 - 7.5	235	808
85 Series					
LT215/85R16 ●	115/112R	6.0	5.5 - 7.0	216	772
LT235/85R16 ●	120/116R	6.5	6.0 - 8.0	235	806
LT235/85R16 W	120/116R	6.5	6.0 - 8.0	235	806
High-Flotation Series					
30x9.50R15LT W	104R	7.5	6.5 - 8.5	236	744
31x10.50R15LT W	109R	8.5	7.0 - 9.0	267	770